700XP Freestanding Gas Pasta Cooker, 2 Wells 24.5 litres

Modular Cooking Range Line 700XP Freestanding Gas Pasta Cooker, 2 Wells 24.5 litres

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



371091 (E7PCGH2KF0)

24,5+24,5-It gas pasta cooker with 2 wells

Short Form Specification

Item No.

High efficiency 21 kW burners. Suitable for natural gas or LPG. Constant starch removal during the cooking process. The tank is pressed in AISI 316-L stainless steel to protect against corrosion. Control panel with gas cock, piezo ignition. Manual water tap. Height adjustable feet in stainless steel. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and veaetables
- High efficiency 23 kW burners in stainless steel with flame failure device and optimized combustion, located below the well.
- No electrical connection needed.
- Water basins are seamlessly welded into the top of the appliance.
- Provided with integrated drip zone on which baskets can be placed for draining purposes.
- 24.5 liters water basins.
- Unit to feature skimming zone for starch removal: improved water quality over time.
- Easy-to-use control panel with gas cock and piezo ignition.
- Safety thermostat to avoid operation without water.
- Continuous water filling regulated through a manual water tap.
- Large drain with manual ball-valve for fast emptying of well.
- ESD available as accessory (installed separately): energy saving device uses heat produced by water drained through the overflow to pre-heat tap-in water up to 60°C, for constant water boiling.
- EnergyControl: unique feature for fine power adjustment to control boiling level and optimize energy consumption.
- Automatic lifting system (optional accessory): 200mm wide unit with two stainless steel basket supports, holding one GN 1/2 basket each, to be placed on either or both sides of machine to provide automatic lifting for four small portion baskets (to be ordered separately). Possibility to memorize nine cooking times through digital control.
- All major compartments located in front of unit for ease of maintenance.
- Unit delivered with four 50 mm legs in stainless steel as standard (all round Stainless steel kick plates as option).

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Water basin in 316-L Stainless steel.
- IPX4 water resistance certification.







Modular Cooking Range Line 700XP Freestanding Gas Pasta Cooker, 2 Wells 24.5 litres

Included Accessories		
• 2 of Door for open base cupboard Optional Accessories	PNC	206350
Junction sealing kit	PNC	206086
• Draught diverter, 150 mm diameter	_	206132
Matching ring for flue condenser, 150 mm diameter	_	206133
 Kit 4 wheels - 2 swivelling with brake - it is mandatory to install base support and wheels 		206135
Flanged feet kit	PNC	206136
 Frontal kicking strip for concrete installation, 800mm 	PNC	206148
 Frontal kicking strip for concrete installation, 1000mm 	PNC	206150
 Frontal kicking strip for concrete installation, 1200mm 	PNC	206151 🗖
 Frontal kicking strip for concrete installation, 1600mm 	PNC	206152
 Frontal kicking strip, 800mm (not for refr-freezer base) 	PNC	206176
 Frontal kicking strip, 1000mm (not for refr-freezer base) 	PNC □	206177
 Frontal kicking strip, 1200mm (not for refr-freezer base) 	PNC □	206178
 Frontal kicking strip, 1600mm (not for refr-freezer base) 	PNC □	206179
 Kit 4 feet for concrete installation (not for 900 line free standing grill) 	PNC	206210
 Flue condenser for 1 module, 150 mm diameter 	PNC	206246
Pair of side kicking strips	PNC □	206249
 Pair of side kicking strips for concrete installation 	PNC	206265
Chimney upstand, 800mm	PNC	206304
Right and left side handrails	PNC □	206307
Back handrail 800mm, Marine	PNC	206308
Energy saving device for pasta cookers	PNC □	206344
Door for open base cupboard	PNC	206350
• Automatic programmable basket lifting system for 24,5lt pasta cookers, 2 lifters	PNC □	206352
 Base support for feet or wheels - 800mm (700/900) 	PNC	206367
Base support for feet or wheels - 1200mm (700/900)	PNC □	206368
 Base support for feet or wheels - 1600mm (700/900) 	PNC □	206369
• Base support for feet or wheels - 2000mm (700/900)	PNC	206370
• Rear paneling - 800mm (700/900)	PNC □	206374
• Rear paneling - 1000mm (700/900)	PNC	206375
• Rear paneling - 1200mm (700/900)	PNC	206376


•	Support frame for 2 pasta cooker basket (700XP)	PNC	206396 🗖
•	Chimney grid net, 400mm (700XP/900)	PNC	206400 🗖
•	2 side covering panels for free standing appliances	PNC	216000 🗖
•	Frontal handrail, 800mm	PNC	216047 🗖
•	Frontal handrail, 1200mm	PNC	216049 🗖
•	Frontal handrail, 1600mm	PNC	216050 🗖
•	Large handrail - portioning shelf, 800mm	PNC	216186 🗆
•	 2 baskets, left and right (105x160x240) for pasta cookers - 700XP and EMPower 	PNC	921020 🗖
•	 2 baskets, left and right (105x105x240) for pasta cookers - 700XP and EMPower 	PNC	921021 🗖
•	False bottom (230x350x60) for pasta cooker baskets - EVO700	PNC	921022 🗖
•	Lid for pasta cookers	PNC	921607 🗖
•	 2 baskets (220x170x240) for pasta cookers - 700XP and EMPower 	PNC	921610 🗖
•	 Full size basket (220x350x240) for pasta cookers - 700XP and EMPower 	PNC	921611 🗖
•	2 half size baskets 105x350 for pasta cookers for 24,51t pasta cookers	PNC	921619 🗖
•	Pressure regulator for gas units	PNC	927225 🗖




Modular Cooking Range Line 700XP Freestanding Gas Pasta Cooker, 2 Wells 24.5 litres



Modular Cooking Range Line 700XP Freestanding Gas Pasta Cooker, 2 Wells 24.5 litres






D = Drain

EQ = Equipotential screw
G = Gas connection

G = Gas connecti WI = Water inlet



Gas

Gas Power:

371091 (E7PCGH2KF0) 23 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG
Gas Inlet: 1/2"

Water:

Drain "D": 1"
Incoming Cold/hot Water line size: 1/2"

Total hardness: 5-50 ppm

Electrolux recommends the use of treated water, based on testing of specific water conditions.

Please refer to user manual for detailed water quality

information.

Key Information:

Usable well dimensions

(width): 250 mm

Usable well dimensions

(height): 300 mm

Usable well dimensions

(depth): 400 mm Well Capacity (MAX): 24.5 lt MAX External dimensions, Width: 800 mm External dimensions, Height: 850 mm External dimensions, Depth: 730 mm Net weight: 65 kg Shipping weight: 79 kg Shipping height: 1130 mm Shipping width: 820 mm Shipping depth: 860 mm

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat

 $0.8 \, \text{m}^3$

insulation fitted.

Shipping volume:

Certification group: N7ECPG

